

SENSIT[®] HXG-2d
COMBUSTIBLE GAS DETECTOR



Detect and find gas leaks fast with **SENSIT HXG-2d**

MADE IN USA

sales@GlobalTestSupply.com



Innovative Detection Solutions

SENSIT-Direct.com

1.888.610.7664

SENSIT[®] HXG-2d

Combustible gas leak detector with digital display for accurate measurement of gases.

SENSIT[®] HXG-2d Combustible gas leak detector is a hand held instrument ideal for detecting and finding the source of natural gas, methane or propane gas leaks.

SENSIT[®] HXG-2d incorporates an advanced low power semi-conductor sensor to measure and display combustible gases in parts per million.

The instrument auto ranges to percent LEL (Lower explosive limit) when concentrations exceed 990 parts per million.

SENSIT[®] HXG-2d also features our unique audible tick control that helps find the source of gas leaks fast. The tick can be easily heard through the speaker located in the back of the instrument.

SENSIT[®] HXG-2d is

- Accurate
- Durable
- Easy to Use
- Easy to Maintain
- Made in USA

Find Gas Leaks Fast!



Standard Features

- Intrinsically Safe Design
- Push-Button Operation
- Field Calibration
- Backlit Display
- Adjustable Alarms
- Long-life, Low-Cost Sensor



Applications

- Locate Small Gas Leaks
- Area Monitoring
- Gas Leak Surveying
- Gas Line Purging
- Chemical Detection
- Arson / Accelerant Detection



Partial List of Gases Detected

- Acetone
- Alcohol
- Ammonia
- Butane
- Ethylene Oxide
- Gasoline
- Halon
- Hydrogen
- Industrial Solvents
- Jet Fuel
- Lacquer Thinner
- Methane
- Natural Gas
- Propane
- Refrigerants

The **SENSIT[®] HXG-2d** cannot be used to check for carbon monoxide (CO) leakage.



TO OPERATE:

1. Press Power
2. Wait 45 Seconds for Automatic Zeroing
3. Begin to Use

Patent Pending

SENSOR SPECIFICATIONS

TYPE	RESOLUTION	RANGE	ACCURACY
LEL	0.1%	0-100% LEL	±10%
PPM*	10ppm	0-990 ppm	±10%

*PPM Optional

PRODUCT SPECIFICATIONS

Size: 3.5" x 10" x 1.6" (8.9 x 25 x 4 cm)
 Weight: 1.2 lb. (0.544 kg)
 Operational Temp: -4 to 104° F (-20 to 40° C)
 Battery Life: Alkaline: Approximately 50 hrs. Continuous



STANDARD KIT

Carrying Pouch
 3 "C" Batteries
 T10 Allen Wrench
 Instruction Manual

KIT OPTIONS

Probe Assembly
 Wrist Strap
 Calibration Kit

OPTIONAL FEATURES

Rechargeable Battery:

NiCad Batteries
 In-Unit Charging
 Universal "Multiple-Country" Charger



710183
 UL 913

Intrinsically Safe for Use in
 Class I, Groups C and D, T3
 Hazardous Locations

AEx ia IIB T3
 IP20
 For use in clean dry areas only.

CE Ex 0891 II 2 G

Ex ib IIB T3 Gb
 IP 20
 ATEX Cert. No. TRAC15ATEX0004X

Only use/store in an area that is clean and dry.

SENSIT® HXG-2d Instruments

SENSIT HXG-2d
Part # 906-00000-08

SENSIT HXG-2dr (with Recharger)
Part # 906-00000-09

SENSIT® HXG-2d Standard Kit Replacement Parts

Soft Carrying Pouch
Part # 360-00006

Wrench (T10)
Part # 360-00105

Sensor Cap with Filter Disc
Part # 882-00036

Retainer Filter (Filter Replacement)
Part # 360-00203

Instruction Manual
Part # 750-00022

SENSIT® HXG-2d Manual Calibration Kits

Methane Calibration Kit (21 liter 2.5% Methane)
Part # 881-00017

Propane Calibration Kit (21 liter 1.1% Propane)
Part # 881-00073

SENSIT® HXG-2d Replacement Cylinders

2.5% Methane/Air (21 Liter)
Part # 315-080012

2.5% Methane/Air (221 Liter)
Part # 315-180013

1.1% Propane/Air (21 Liter)
Part # 315-080022

1.1% Propane/Air (221 Liter)
Part # 315-180004