


NOTE

1. OUTPUT SHAFT POSITION : HORIZONTAL
2. ROTATION : VIEWED FROM OUTPUT SHAFT END C.W
3. END PLAY : 1) ROTOR : 0.8mm MAX.
2) SPINDLE : 0.8mm MAX.
4. LUBRICATE : 1) GEAR BOX - GREASE
2) MOTOR - MINERAL OIL
5. NAME PLATE POSITION : SURFACE 'B'
6. MARK THE FOLDING PART AS USING WHITE INK
7. SCREW FASTENING TORQUE : 8Kgf·cm
8. AUDIBLE NOISE : 70 dB MAX.
1) 50cm DISTANCE FROM SPINDLE END SIDE
2) SOUND LEVEL METER 'A' SCALE
3) AMBIENT NOISE : 25dB MAX
4) AT RATED VOLTAGE, RATED FR.FQUENCY (NO LOAD)

NAME PLATE

SPG Co., Ltd. **CE**
 MODEL : ISG-3240ENA
 AC 230V 50Hz
 IDLE : 0.43A 5.6RPM
 INT. DUTY T.P.L. 17AM031 TI
 MADE IN KOREA



VIEW 'C'

| NO. | PART NAME | MATERIAL | Q'TY | DESCRIPTION | REMARK |
|-----|---------------------------|---------------|------|----------------|--------|
| 6 | NAME PLATE | TETRON SILVER | 1 | 38 * 25 | |
| 5 | SCREW(WITH SPRING WASHER) | SWCH10A | 2 | M/S PH ⊕ M4*52 | MFZnl |
| 4 | GEAR BOX ASS'Y | | 1 | △ 1:513 | |
| 3 | STATOR ASS'Y | | 1 | 40T | |
| 2 | ROTOR ASS'Y | | 1 | 40T | |
| 1 | BRACKET ASS'Y | | 1 | OPEN TYPE | |

| | | | |
|---------------------------|---------------------------|---|------------------------------|
| 2004.02.03 | N. Y. KIM | CHANGE : RATIO 1:532 --> 1:513 | |
| 2003.09.27 | Y. M. WON | CHANGE : NAME PLATE | CE MARK |
| 2002.08.13 | N. Y. KIM | CHANGE : INPUT, OUTPUT, SHAFT DIMENSION | |
| 날 짜 DATE | 서 명 SIGN | 변 경 내 용 NOTE | 변 경 이 유 REVISION |
| 재 질 MATERIAL | 표 면 처 리 SURFACE FINISH | 척 도 SCALE | 1/1 공 차 TOLERANCE ±1.0 |
| 제 도 DRAWN | 설 계 DESIGN | 검 도 CHECK | 승 인 APPR. |
| | | | 도 명 NAME |
| GEARED MOTOR ASS'Y | | | |
| ISG-3240ENA(1:513) | | | |
| SPG Co., Ltd. | | 작성 일 DATE | 2004.02.03 |
| | | 도 번 DWG NO. | A-46-0455-03 △ |