



© copyright by DIRAK / Germany



<b>a) Rod-Latch RH/LH</b>	<b>208-9024</b>
<b>b) Inserts with screw and wave washer</b>	
Square 7	<b>208-9218</b>
Square 8	<b>208-9219</b>
Double bit 3 pin	<b>208-9220</b>
Double bit 5 pin	<b>208-9221</b>
Triangular 7	<b>208-9222*</b>
Handles stainless steel on page 7-045.	
Swinghandles stainless steel on page 7-060.	
Swinghandles PA on pages 3-150 and 3-153.	
<b>c) Escutcheon</b>	<b>208-9504</b>
<b>d) Cams</b>	
A in mm / inch	
22 / 0.866	<b>200-0518</b>
24 / 0.945	<b>200-0520</b>
26 / 1.024	<b>200-0522</b>
28 / 1.102	<b>200-0524</b>
30 / 1.181	<b>200-0526</b>
32 / 1.260	<b>200-0528</b>
36 / 1.417	<b>200-0532</b>
54 / 2.126	<b>200-0550</b>
<b>e) Adapter with screw</b>	<b>208-9406</b>
<b>f) Rod with Ramp-Shoe</b> (on page 7-070)	
<b>g) Rod Guide</b> (on page 3-910)	<b>208-1501.03</b>
Please order 2 pcs. per rod.	
<b>g<sub>1</sub>) Rod Guide (half), stainless steel</b> (on page 3-910)	<b>208-1502.04-00001</b>
<b>Attention:</b> For each Rod Guide you need two halves, so 4 per rod.	
<b>Optional:</b>	
<b>h) Grounding/earthing device</b> (on page 3-910)	<b>208-1201.04</b>
Water- and dust-tight according to IP65 by:	
<b>i) O-Ring for inserts</b>	<b>208-1801</b>
<b>k) O-Ring for escutcheon; please order 2 pcs.</b>	<b>208-1802</b>
<b>* Quantity and delivery time on request.</b>	

Rod-Latch system.  
• RH or LH application.  
• The latch can be combined with escutcheons, handles or Swinghandles.  
• Detailed dimensions of cutout, version C on page 3-010.

**Material:**

- a)  
• **Latch:** AISI 316  
• **Rods:** AISI 304  
b)  
• **Inserts:** stainless steel.  
c)  
• **Escutcheon:** AISI 316  
d)  
• **Cam:** AISI 304  
e)  
• **Adapter:** AISI 304  
f)  
• **Rod:** AISI 304  
• **Ramp-Shoe:** PA, black  
g)  
• **Rod Guide:** PA, black  
g<sub>1</sub>)  
• **Rod Guide:** AISI 316  
h)  
• **Grounding/earthing device:** AISI 304

12/21/06

© copyright by DIRAK / Germany

