

- High flash power from two consecutive flashes
- High light intensity
- High impact resistance to 20 Joules



Wire guard (accessory)



Plastic bracket (accessory)



Flange for tube mounting (accessory)

TECHNICAL SPECIFICATIONS:

Dimensions (Diameter x Height):	142 mm x 220 mm
Housing:	PC/ABS-Blend
Dome:	PC, transparent
Fixing:	Base mounting, Bracket mounting (accessory), Tube mounting (accessory)
Connection:	Screwable connection with wire protection 0.5 - 2.5 mm ²
Cable entry:	Cable diameter 5 - 7 mm
Flash energy:	15 Ws
Flash frequency:	c. 1 Hz
Power supply frequency:	50/60 Hz
Life duration:	4 x 10 ⁶ flashes

ORDER SPECIFICATIONS:

Voltage	24 V [≐]	115 V [~]	230 V [~]
Current consumption	800 mA	300 mA	200 mA
red	838 100 55	838 100 67	838 100 68
yellow	838 300 55	838 300 67	838 300 68

ACCESSORIES:

Plastic bracket for wall mounting	975 883 06
Flange for tube mounting max. 25.3 mm	975 883 02
Wire guard	975 883 08

TECHNICAL DIAGRAMS:

see page 287

