

# Indicators



## VACUUM GAUGE

NBR	FKM	Vacuum gauge	NBR	FKM	Vacuum gauge
10	-	Scale 0 ÷ 100 kPa (1 bar)	11	-	Scale 0 ÷ 100 kPa (1 bar)

## PRESSURE GAUGE

NBR	FKM	Pressure gauge	NBR	FKM	Pressure gauge
30	-	Scale 0 ÷ 600 kPa (6 bar)			
31	-	Scale 0 ÷ 1,2 MPa (12 bar)			
32	-	Scale 0 ÷ 600 kPa (6 bar)			
33	-	Scale 0 ÷ 1,2 MPa (12 bar)			

## DIFFERENTIAL INDICATORS

NBR	FKM	Differential VISUAL indicator	NBR	FKM	Differential ELECTRICAL indicator
U0	W0	Setting 130 kPa (1,3 bar)	N0	S0	Setting 130 kPa (1,3 bar)

NBR	FKM	Differential VISUAL indicators	NBR	FKM	Differential ELECTRICAL indicators
5B	AB	Setting 130 kPa (1,3 bar)			
5C	AC	Setting 200 kPa (2 bar)			
5D	AD	Setting 250 kPa (2,5 bar)			
5E	AE	Setting 500 kPa (5 bar)			
5F	AF	Setting 800 kPa (8 bar)			

NBR	FKM	Differential ELECTRICAL indicators	NBR	FKM	Differential ELECTRICAL indicators
6B	CB	Setting 130 kPa (1,3 bar)			
6C	CC	Setting 200 kPa (2 bar)			
6D	CD	Setting 250 kPa (2,5 bar)			
6E	CE	Setting 500 kPa (5 bar)			
6F	CF	Setting 800 kPa (8 bar)			

**VACUUM SWITCH**

NBR	FKM	Vacuum switch		
91	-	Setting 20 kPa (0,2 bar)		ATEX 3 GD EEx e T6 
S8	-	Setting 25 kPa (0,25 bar)		

**PRESSURE SWITCH**

NBR	FKM	Pressure switch		
P4	-	Setting 130 kPa (1,3 bar)		ATEX 3 GD EEx e T6 
P1	-	Setting 150 kPa (1,5 bar)		
P6	-	Setting 200 kPa (2 bar)		
R8	-	Setting 150 kPa (1,5 bar)		

NBR	FKM	Differential ELECTRICAL indicators with LED (24V) for visual indication		
7B	EB	Setting 130 kPa (1,3 bar)		Recommended tightening torque 90 Nm 
7C	EC	Setting 200 kPa (2 bar)		
7D	ED	Setting 250 kPa (2,5 bar)		
7E	EE	Setting 500 kPa (5 bar)		
7F	EF	Setting 800 kPa (8 bar)		

NBR	FKM	Differential ELECTRICAL indicators with THERMOSTAT 30°C		
T0	DB	Setting 130 kPa (1,3 bar)		Recommended tightening torque 90 Nm 
T1	DC	Setting 200 kPa (2 bar)		
T6	DD	Setting 250 kPa (2,5 bar)		
T2	DE	Setting 500 kPa (5 bar)		
T3	DF	Setting 800 kPa (8 bar)		

NBR	FKM	Differential VISUAL ELECTRICAL indicators		
70	E0	Setting 130 kPa (1,3 bar)		Recommended tightening torque 90 Nm 
71	E1	Setting 200 kPa (2 bar)		
76	E6	Setting 250 kPa (2,5 bar)		
72	E2	Setting 500 kPa (5 bar)		
73	E3	Setting 800 kPa (8 bar)		

NBR	FKM	Differential ELECTRICAL indicator		
XD	-	Setting 240 kPa (2,4 bar)		

Technical data subject to variations without prior notice. Clogging indicators 10/2016