



Specifiche Tecniche

Alimentazione

- Valori nominali: 85-250 Vca-cc 50/60 Hz
- Assorbimento: 5VA (max)

Ingressi

- 2 ingressi di abilitazione gestione remota ENABLE: COM-EN1-EN2
- Collegamenti su morsettiere estraibili

Uscite

- 1 relay di guasto sonde o anomalia funzionamento (FAULT)
- Relay di uscita con contatti da 5A-250Vca-res COSΦ=1
- 2 uscite M1-M2: 85-250Vac max 5A max 50/60Hz

Test e prestazioni

- Costruzione in accordo alle normative CEI EN61000-4-4
- Rigidità dielettrica: 1500 Vca per 1 minuto: alimentazione-relè fault, alimentazione-remote
- Temperatura di lavoro: da -20°C a + 60°C
- Umidità ammessa: 90% senza condensa
- Contenitore in NORYL UL 94V0 autoestinguente
- Opzione: tropicalizzazione
- Pellicola frontale policarbonato IP65

Visualizzazione e gestione dati

- Led allarme: undercurrent, overcurrent
- Led running, intellifan, remote, local
- Led On prg, cal
- AUTO-TUNING iniziale di impostazione protezione motori
- Tasto frontale per lo START/STOP manuale dei motori
- Tasto frontale per il reset degli allarmi
- Accesso alla programmazione tramite tasto frontale
- Funzione Intellifan

Dimensioni

- 100 x 100 mm DIN 43700 prof. 131 mm (compreso morsettiera)
- Foro pannello 92 x 92 mm

Technical Specifications

Power supply

- Rated values: 85-250 Vac-dc 50/60 Hz
- Burden: 5VA (max)

Inputs

- 2 inputs enabling remote control ENABLE: COM-EN1-EN2
- Removable rear terminals

Outputs

- 1 fault sensor or operating failure (FAULT)
- Output relay with 5A-250Vac-res COSΦ=1 contacts
- 2 outputs M1-M2: 85-250Vca max 5A max 50/60Hz

Tests and performances

- Assembling in accordance with CEI EN61000-4-4
- Dielectric strength: 1500 Vac for 1 minute: supply-relay fault, supply-remote
- Ambient operating temperature: from -20°C to + 60°C
- Humidity: 90% non-condensing
- Self-extinguishing housing NORYL UL 94V0
- Option: tropicalization
- Polycarbonate frontal film IP65

Displaying and data management

- Alarm leds: undercurrent, overcurrent
- Running, intellifan, remote, local leds
- On Prg, cal leds
- Starting AUTO-TUNING for motor protection set-up
- Front key for manual START/STOP of the motors
- Front alarm reset key
- Programming access through front key
- Intellifan function

Dimensions

- 100 x 100 mm DIN 43700 depth 131 mm (terminals included)
- Panel cut-out 92 x 92 mm

Collegamenti elettrici | Electrical connections

