

# STFX - Flexible PTFE Heaters

## Flexible Design, Certified, Flexible Risers

Ratings 500-3700 Watts.

Voltage: 1 phase 230 V or 3-phase 400 V

\* Also available in 3-phase 230 V

### Standard sizes

#### 1 phase 230 Volts

	A	B	Th.	W/cm <sup>2</sup>
0,5kW	230	180	35	1,5
1kW	230	260	35	1,5
1,5kW	260	300	35	1,5
1,5kW	320	260	35	1,5
1,5kW	350	220	35	1,5
1,5kW	420	210	35	1,5
2kW	340	280	35	1,5
2kW	540	200	35	1,5
2kW	290	370	35	1,5
2kW	245	410	35	1,5
3kW	320	420	35	1,5
3kW	410	325	35	1,5
3kW	535	270	35	1,5
3kW	640	240	35	1,5
3kW	680	225	35	1,5
3kW	880	195	35	1,5
3kW	1050	160	35	1,5
4kW	340	280	50	1,5
4kW	540	200	50	1,5
4kW	290	370	50	1,5
4kW	245	410	50	1,5
6kW	320	420	50	1,5
6kW	410	325	50	1,5
6kW	535	270	50	1,5
6kW	640	240	50	1,5
6kW	680	225	50	1,5
6kW	880	195	50	1,5
6kW	1050	160	50	1,5

#### 3 phase 400 Volts

	A	B	Th.	W/cm <sup>2</sup>
2,25kW	335	340	35	1,5 *
2,25kW	400	280	35	1,5 *
2,25kW	460	255	35	1,5 *
2,25kW	530	230	35	1,5 *
2,25kW	625	215	35	1,5 *
2,25kW	1030	150	35	1,5 *
3kW	320	420	35	1,5 *
* 3kW	410	325	35	1,5 *
3kW	535	270	35	1,5 *
3kW	640	240	35	1,5 *
3kW	680	225	35	1,5 *
3kW	880	195	35	1,5 *
3kW	1050	160	35	1,5 *
3,7kW	320	420	35	2,0
3,7kW	410	325	35	2,0
3,7kW	535	270	35	2,0
3,7kW	640	240	35	2,0
3,7kW	680	225	35	2,0
3,7kW	880	195	35	2,0
3,7kW	1050	160	35	2,0

### Options:

Overheat Protection OHP 1 or OHP 2

L-bent Bottom Mount

