



Bestell-Nr.	Code	Anschluss-gewinde	max. Volumenstrom l/min	max. Druck bar	min. zul. Δp bar	Betriebstemp. °C	Gewicht Kg	Material Körper	zugehörige Kontermutter	
240-114-01000	FT2257/2-14	1/4"	max. 400bar - 14l/min	400	1600	-20°/+130°	0,20	1.4401 - AISI 316	240-130-01050	240-130-01350
240-114-01050	FT2257/2-38	3/8"	max. 400bar - 38l/min	400	1600		0,38		240-130-01100	240-130-01400
240-114-01100	FT2257/2-12	1/2"	max. 400bar - 54l/min	400	1600		0,60		240-130-01150	240-130-01450
240-114-01150	FT2257/2-34	3/4"	max. 400bar - 80l/min	400	1600		1,25		-	240-130-01500
240-114-01200	FT2257/2-100	1"	max. 320bar - 195l/min	320	1300		2,55		-	240-130-01550
240-114-01250	FT2257/2-114	1-1/4"	max. 320bar - 198l/min	320	1300		3,00		-	240-130-01600
240-114-01300	FT2257/2-112	1-1/2"	max. 320bar - 210l/min	320	1300		4,22		-	-
240-114-01350	FT2257/2-200	2"	max. 320bar - 195l/min	320	1300		7,30		-	-

Type	Bemessung									
	A	B	C	D	E	ØF	ØF1	G	H	SW
14	1/4"G	12,5	49	71	78	27	50	17	M20x1	20
38	3/8"G	12,5	59	84	93	33	70	19,5	M25x1,5	25
12	1/2"G	15,5	68	97	107	38	80	21	M30x1,5	30
34	3/4"G	17	86	120,5	132,5	47	100	26,5	M40x1,5	40
100	1"G	20	105	151,5	167,5	58	120	35	M50x1,5	50
114	1 1/4"G	22	120	156,5	172,5	58	120	35	M50x1,5	55
112	1 1/2"G	24	134	167	181	58	120	35	M55x2	65
200	2"G	27	150	188	202	108	/	44	M65x2	75



