

Valve grinding tool with 2 suction discs

- 8 mm bore reception
- For the grinding of the valve seats for repair work
- The detention of the device body is automatically generated via a transmission, the typical right left wing movement used in grinding
- Gives you convenient and rapid seat grinding with the drill between approx. 500-1.000 rpm



Item	L mm	Replacement plate Ø 22 mm	Replacement plate Ø 28 mm	Weight
150.1165	130.0	150.1166	150.1167	442

Precision straightedge

- For the inspection and the exact working on cylinder heads
- In accordance with DIN 874/1
- Double T profile rail with rear 5 hand slots
- On edge and flat sides examination process
- Hanging hole
- Steel



Item	L mm	B mm	H mm	Weight
152.1090	300.0	36.0	16.0	2.10

Precision straightedge

- In accordance with DIN 874/00
- Hand warmth protection
- Test area precise and finely engineered
- Flatness tolerance for highest accuracy
- For controlled and test working in the light gap procedure
- Hardened
- Stainless steel



Item	L mm	H mm	Weight
300.0630	50.0	25.0	40
300.0631	75.0	25.0	60
300.0632	100.0	25.0	80
300.0633	125.0	25.0	100
300.0634	150.0	25.0	120
300.0635	200.0	25.0	160
300.0636	300.0	25.0	240
300.0637	400.0	25.0	320
300.0638	500.0	25.0	400
300.0639	600.0	25.0	480

Piston ring pliers


- For the removal and replacement of piston rings
- Suitable for most cars and vans
- Plastic coated handle
- Self closing pliers
- Special steel



Item	L mm	Weight
150.1179	221.0	210

Piston ring pliers

- For the safe disassembly and assembly of piston rings
- Chrome plated
- With single component handle
- Special tool steel



Item	Ø mm	A mm	D mm	L mm	Weight
150.1175	50,0-110,0	0,0-110,0	60,0	210,0	305
150.1176	80,0-120,0	0,0-120,0	60,0	220,0	340
150.1177	110,0-160,0	0,0-158,0	60,0	280,0	445

Cylinder honing machine

- For honing / deburring of cylinders, bearings, bores, pipes, etc.
- Interchangeable honing
- Automatic spigot end and exact honing
- Flexible drive shaft for air or electric drills
- Special steel

Application range: Automotive brake and clutch cylinders, engine cylinders of motor cycles, lawn mowers, outboard motors, hydraulic cylinders, marine and industrial engines, etc.



Item	Ø mm	Arm	Honing stone set	Weight
150.1180	18 - 63	2	150.1181	0.90
150.1185	19 - 69	3	150.1186	1.30
150.1190	32 - 89	3	150.1191	1.40
150.1195	51 - 177	3	150.1196	1.90