

Scheda dati

050PE8C

Plafoniera lineare fluorescente, 240V, 50/60HZ, 400 lux,
L 368 mm, con connettore



Caratteristiche

Gamma	050 Segnalazione ed Illuminazione Quadri Elettrici
Componente	Plafoniere elettroniche fluorescenti
Tipo	Plafoniera lineare fluorescente, 240V, 50/60HZ, 400 lux
Codice	050PE8C
Descrizione	Plafoniera lineare fluorescente, 240V, 50/60HZ, 400 lux, L 368 mm, con connettore
Colore	Grigio RAL7035
Peso - gr	392,000
Tariffa doganale	85122000
GTIN	8052878049201

Dati tecnici

Approvals	CE
Approvals	ETL INTERTEK (only 050PE86C,050PE136C)
Compliance with standards	IEC-EN60598-1,IEC-EN60598-2-1,IEC-EN61347-1
Compliance with standards	IEC-EN61347-2-13, IEC-EN62471, IEC-EN55015,
Compliance to EMC standards	IEC-EN61547, IEC-EN61000-3-2, IEC-EN61000-3-3
Compliance to directives	2014/35/UE, 2006/42/EC, 2014/30/UE, RoHS 2002/95
Operating temperatures	-10° ± +50°C
Environmental operating values	"all climates" +40°C and 92% RH
Protection degree	IP30 (IEC-EN60529)
Protection against impact	IK06 (IEC-EN62262)
Housing material	PC Polycarbonate
Overvoltage category	Class II (IEC-EN61140)
Neon tube brightness - Power consumption	Lux 400 - 8W
Operating voltage tolerance	+10% / -20%
Neon tube electrical life	8.000 hours
Neon tube type and colour temperature	T5 - 6400K
Rated insulation voltage	Ui 300V - Uimp 2.5KV
On-Off switch	Built-in
Light distribution	Rotation of 180° - adjustable
Power supply connector	050C7V2 included, suitable for single lamp wiring
Power supply connector	or sequential wiring of max n°5 lamps
Light up possibility	Through door limit switch - 050F02S

Scheda dati

050PE8C

Plafoniera lineare fluorescente, 240V, 50/60HZ, 400 lux,
L 368 mm, con connettore

Accessory	050KFM Magnetic mounting kit
Spare parts	Neon tube 050TNE8(8W),050TNE13(13W),050TNE21(21W)
Warranty period	18 months

Scheda dati

050PE8C

Plafoniera lineare fluorescente, 240V, 50/60HZ, 400 lux,
L 368 mm, con connettore

Disegni tecnici

