



SENSORS: MOTOSONIC 810



With the ultrasonic level sensor MOTOSONIC you enter a new dimension of measuring content levels because measurement of the liquid level in a tank is done contactless by using ultrasonic technology.

The flexible MOTOSONIC can be used for quite a high number of liquids in various tank shapes.

The ultrasonic level sensor MOTOSONIC generates a high frequency sound wave to measure the time, the wave needs to run to the fluid level and back, after it was reflected by the liquid surface. Based on the measured time and the speed of sound, the distance between the sensor and the liquid surface can be calculated, and by this means the tank content as well.



SENSORS: MOTOSONIC 810

It is important for the calculation to take also the tank shape into account, just as waves on the surface of the liquid or possibly upcoming reflections in the tank. Compared with classical level sensors, measurement with the ultrasonic method is very precise, because distance is detected with an accuracy of ± 2.5 mm and a resolution of 1.8 mm.

Moreover, measurement is done contactless to the medium, what avoids abrasion of mechanical parts and increases the lifetime of the sensor. Fixing on the tank is realised by a 54 mm 5-hole-flange or a 80 mm 6-hole-flange adapter (other flanges can also be offered on request).

The electrical connection is realised with an Delphi-connector. By programming a table of interpolation values into the sensor, tank contents of various tank shapes can exactly be displayed on standard gauges.

MOTOSONIC 810 with Three-Wire Connection

- Three-Wire Connection: Output signal: 0.5 to 4.5 Volts

Technical specifications

Operating voltage:	10 to 30 Volts
Output signal:	3-Wire: 0.5 to 4.5 Volts (Output impedance 1k to 20 kOhm)
Max. measuring length:	810 mm
Blind area:	50 mm
ESD:	15 KV
Mechanical shock:	18 G Shock
Vibration:	4 G, 8 hours each 3 directions in space
Acoustic cone angle:	6 degrees
Operation temperature:	-40 to +85 °C

Length	Damping	Characteristic Line	Mounting	Part No.
460 mm	middle	linear	54 mm 5-hole-flange	608 043 1017
500 mm	middle	linear	54 mm 5-hole-flange	608 043 1007
541 mm	middle	linear	54 mm 5-hole-flange	608 043 1001
700 mm	fast	linear	54 mm 5-hole-flange	608 043 1013
810 mm	middle	linear	54 mm 5-hole-flange	608 043 1014

MOTOMETER

MOTOMETER GmbH

Fritz-Neuert-Straße 27 | 75181 Pforzheim/Germany

Phone +49 7231 42909-300 | Fax +49 7231 42909-305

E-Mail info@motometer.de | www.motometer.de