

# Lightweight Flexible Stainless Steel Coupling

## Style 475



17.14



1 – 4"/25 – 165.1 mm

### 1.0 PRODUCT DESCRIPTION

#### Available Sizes

- 1 – 4"/25 – 165.1 mm

#### Pipe Material

- Stainless Steel Type 316 (CF8M)

#### Maximum Working Pressure

- Working pressure dependent on material, wall thickness and size of pipe

#### Operating Temperature Range

- Dependent on gasket selection from Section 3.0

#### Function

- Provides a flexible pipe joint which allows for expansion, contraction and deflection

#### Pipe Preparation

- Victaulic Original Groove System (OGS)

#### Application

- This product joints standard roll grooved and cut grooved pipe

### 2.0 CERTIFICATION/LISTINGS

#### NOTE

- See Victaulic [Publication 02.06](#) for potable water approvals if applicable.

ALWAYS REFER TO ANY NOTIFICATIONS AT THE END OF THIS DOCUMENT REGARDING PRODUCT INSTALLATION, MAINTENANCE OR SUPPORT.

System No.		Location	
Submitted By		Date	

Spec Section		Paragraph	
Approved		Date	



### 3.0 SPECIFICATIONS – MATERIAL

---

**Housing:** Type 316 stainless steel, conforming to ASTM-A351, A743, and A744 Grade CF8M.

**Housing Coating:** None

**Standard Gaskets:**

**Grade “EW” EPDM**

EPDM (Green “W” color code). Temperature -30°F to +230°F/-34°C to +110°C. May be specified for hot water service within the specified temperature range plus a variety of dilute acids, oil-free air and many chemical services. WRAS-certified material with approved microbiological resistance to BS 6920 for cold and hot potable water service up to +149°F/+65°C. UL Classified in accordance with ANSI/NSF 61 for cold +73°F/+23°C and hot +180°F/+82°C potable water service and ANSI/NSF 372. NOT COMPATIBLE FOR PETROLEUM SERVICES.

**Optional Gasket: (specify choice<sup>1</sup>)**

**Grade “E” EPDM**

EPDM (Green stripe color code). Temperature range -30°F to +230°F/-34°C to +110°C. May be specified for cold and hot water service within the specified temperature range plus a variety of dilute acids, oil free air and many chemical services. UL Classified in accordance with ANSI/NSF 61 for cold +73°F/+23°C and hot +180°F/+82°C potable water service and ANSI/NSF 372. NOT COMPATIBLE FOR PETROLEUM SERVICES.

**Grade “T” Nitrile**

Nitrile (Orange stripe color code). Temperature range 20°F to +180°F/29°C to +82°C. May be specified for petroleum products, air with oil vapors, vegetable and mineral oils within the specified temperature range. Not compatible for hot water services over +150°F/+66°C or for hot dry air over +140°F/+60°C.

**Grade “O” Fluoroelastomer**

Fluoroelastomer (Blue stripe color code). Temperature range +20°F to +300°F/-7°C to +149°C. May be specified for many oxidizing acids, petroleum oils, halogenated hydrocarbons, lubricants, hydraulic fluids, organic liquids and air with hydrocarbons.

**Grade “A” White Nitrile:**

White nitrile (White gasket). Temperature range +20°F to +180°F/-7°C to +82 °C. No carbon black content. May be used for food services. Meets FDA requirements and conforms to CFR Title 21 Part 177.2600.

<sup>1</sup> Services listed are General Service Guidelines only. It should be noted that there are services for which these gaskets are not compatible. Reference should always be made to the latest [Victaulic Gasket Selection Guide](#) for specific gasket service guidelines and for a listing of services which are not compatible.


**Hardware:**

**Bolts:** Type 316 stainless steel, oval neck track bolts and heavy hex nuts with chemical and physical properties of ASTM F-593, Group 2, Condition CW and special anti-galling coating.

**Nuts:** Heavy hex nut, ASTM F-594, Group 2 (316 stainless steel), condition CW with special antigalling coating.

## 4.0 DIMENSIONS

### Style 475



Typical for all sizes

Size		Pipe End Separation <sup>2</sup>	Deflect. From CL <sup>2</sup>		Bolt/Nut		Dimensions			Weight
Nominal inches DN	Actual Outside Diameter inches mm	Allowable inches mm	Per Cplg. Deg.	Pipe In./Ft. mm	Qty.	Size inches mm	X inches mm	Y inches mm	Z inches mm	Approximate (Each) lb kg
1 DN25	1.315 33.7	0 – 0.06 0 – 1.6	2° – 43'	0.57 48	2	3/8 x 2	2.13 54	3.98 101	1.63 41	1.3 0.6
1 1/4 DN32	1.660 42.4	0 – 0.06 0 – 1.6	2° – 10'	0.45 38	2	3/8 x 2	2.46 63	4.45 113	1.72 44	1.4 0.6
1 1/2 DN40	1.900 48.3	0 – 0.06 0 – 1.6	1° – 56'	0.40 33	2	3/8 x 2	2.72 69	4.52 115	1.72 44	1.5 0.7
2 DN50	2.375 60.3	0 – 0.06 0 – 1.6	1° – 30'	0.32 26	2	3/8 x 2	3.30 84	5.03 128	1.80 46	1.7 0.8
2 1/2 DN65	2.875 73.0	0 – 0.06 0 – 1.6	1° – 15'	0.26 22	2	3/8 x 2	3.88 99	5.59 142	1.80 46	1.9 0.9
DN76.1	3.000 76.1	0 – 0.06 0 – 1.6	1° – 12'	0.25 21	2	3/8 x 2	4.00 102	5.73 146	1.80 46	1.9 0.9
3 DN80	3.500 88.9	0 – 0.06 0 – 1.6	1° – 1'	0.21 18	2	1/2 x 2 3/4	4.50 114	6.67 169	1.80 46	2.9 1.3
4 DN100	4.500 114.3	0 – 0.13 0 – 3.2	1° – 35'	0.33 28	2	1/2 x 2 3/4	5.75 146	7.96 202	2.00 51	4.2 1.9
DN139.7	5.500 139.7	0 – 0.13 0 – 3.2	1° – 18'	0.27 23	2	1/2 x 2 3/4	6.81 173	8.97 228	2.00 51	4.9 2.2
DN165.1	6.500 165.1	0 – 0.13 0 – 3.2	1° – 6'	0.23 19	2	5/8 x 3 1/2	7.87 200	10.53 268	2.00 51	6.8 3.1

<sup>2</sup> Allowable Pipe End Separation and Deflection figures show the maximum nominal range of movement available at each joint for standard roll grooved pipe. Figures for standard cut grooved pipe may be doubled. These figures are maximums; for design and installation purposes these figures should be reduced by: 50% for 3/4 – 3 1/2"/20 – 90 mm; 25% for 4"/100 mm and larger.

## 5.0 PERFORMANCE

### Performance on ANSI wall thicknesses

Nominal Size inches DN	Actual Outside Diameter inches mm	Pipe Wall Thickness		Groove Type	Maximum	
		inches mm	ANSI Schedule Number		Working Pressure psi kPa	End Load lb N
1 DN25	1.315 33.7	0.179 4.9	80S	C	500 3447	679 3021
		0.133 3.6	40S	Std/C	500 3447	679 3021
		0.109 2.8	10S	RX	350 2413	475 2114
		0.065 1.7	5S	RX	225 1551	306 1359
1 1/4 DN32	1.660 42.4	0.191 4.9	80S	C	500 3447	1082 4813
		0.140 3.6	40S	Std/C	500 3447	1082 4813
		0.109 2.8	10S	RX	350 2413	757 3369
		0.065 1.7	5S	RX	225 1551	487 2166
1 1/2 DN40	1.900 48.3	0.200 5.1	80S	C	500 3447	1418 6306
		0.145 3.7	40S	Std/C	500 3447	1418 6306
		0.109 2.8	10S	RX	350 2413	992 4414
		0.065 1.7	5S	RX	225 1551	638 2837
2 DN50	2.375 60.3	0.218 5.5	80S	C	500 3447	2215 9853
		0.154 3.9	40S	Std/C	500 3447	2215 9853
		0.109 2.8	10S	RX	350 2413	1550 6897
		0.065 1.7	5S	RX	225 1551	997 4433
2 1/2 DN65	2.875 73.0	0.276 7.0	80S	C	500 3447	3246 14438
		0.203 5.2	40S	Std/C	500 3447	3246 14438
		0.120 3.1	10S	RX	350 2413	2272 10106
		0.083 2.1	5S	RX	232 1600	1506 6699
3 DN80	3.500 88.9	0.300 7.6	80S	C	500 3447	4811 21398
		0.216 5.5	40S	Std/C	500 3447	4811 21398
		0.120 3.1	10S	RX	350 2413	3367 14978
		0.083 2.1	5S	RX	232 1600	2232 9929
4 DN100	4.500 114.3	0.337 8.6	80S	C	500 3447	5169 22994
		0.237 6.0	40S	Std/C	500 3447	5169 22994
		0.120 3.1	10S	RX	350 2413	4771 21224
		0.083 2.1	5S	RX	232 1600	3690 16413

**NOTES**

- RX = Roll Set for light wall stainless steel pipe marked with the prefix "RX"
- Std = Standard roll set marked with the prefix "R"
- C = Cut groove

## 5.1 PERFORMANCE

### Performance on ISO wall thicknesses

Nominal Size inches DN	Actual Outside Diameter inches mm	Pipe Wall Thickness inches mm	Groove Type	Maximum	
				Working Pressure kPa psi	End Load N lb
1 DN25	1.315 33.7	0.177 4.5	C	3447 500	3021 679
		0.126 3.2	Std	2930 425	3021 679
		0.102 2.6	RX	2241 325	1963 441
		0.091 2.3	RX	2065 300	1812 407
		0.079 2.0	RX	1724 250	1510 340
		0.063 1.6	RX	1551 225	1359 306
1 1/4 DN32	1.660 42.4	0.197 5.0	C	3447 500	4813 1082
		0.142 3.6	Std/C	3447 500	4813 1082
		0.126 3.2	Std	2930 425	4091 920
		0.102 2.6	RX	2241 325	3129 703
		0.079 2.0	RX	1724 250	2407 541
		0.063 1.6	RX	1551 225	2166 487
1 1/2 DN40	1.900 48.3	0.197 5.0	C	3447 500	6306 1418
		0.142 3.6	Std/C	3275 475	5991 1347
		0.126 3.2	Std	2758 400	5045 1134
		0.102 2.6	RX	2241 325	4099 921
		0.079 2.0	RX	1724 250	3153 709
		0.063 1.6	RX	1551 225	2837 368
2 DN50	2.375 60.3	0.220 5.6	C	3447 500	9853 2215
		0.157 4.0	Std/C	3447 500	9853 2215
		0.142 3.6	Std	3103 450	8868 1994
		0.126 3.2	Std	2758 400	7882 1772
		0.114 2.9	Std	2413 350	6897 1551
		0.102 2.6	RX	2241 325	6404 1440
		0.091 2.3	RX	2065 300	5912 1329
		0.079 2.0	RX	1724 250	4927 1108
		0.063 1.6	RX	1551 225	4433 997

**NOTES**

- RX = Roll Set for light wall stainless steel pipe marked with the prefix "RX"
- Std = Standard roll set marked with the prefix "R"
- C = Cut groove

5.1 PERFORMANCE (Continued)

Performance on ISO wall thicknesses

Nominal Size inches DN	Actual Outside Diameter inches mm	Pipe Wall Thickness inches mm	Groove Type	Maximum	
				Working Pressure kPa psi	End Load N lb
DN76.1	3.000 76.1	0.280 7.1	C	3447 500	15721 3534
		0.252 6.4	C	3447 500	15741 3534
		0.197 5.0	Std/C	2930 425	13363 3004
		0.157 4.0	Std	2758 400	12577 2827
		0.142 3.6	Std	2586 375	11791 2651
		0.122 3.1	Std	2413 350	11004 2474
		0.114 2.9	RX	2241 325	10219 2297
		0.102 2.6	RX	2065 300	9433 2121
		0.091 2.3	RX	1724 250	7861 1767
		0.083 2.1	RX	1600 232	7295 1640
		0.079 2.0	RX	1600 232	7295 1640
3 DN80	3.500 88.9	0.315 8.0	C	3447 500	21398 4811
		0.220 5.6	Std/C	3447 500	21398 4811
		0.157 4.0	Std	2758 400	17119 3848
		0.142 3.6	Std	2586 375	16049 3608
		0.126 3.2	Std	2313 350	14979 3367
		0.114 2.9	RX	20241 325	13909 3127
		0.102 2.6	RX	2065 300	12839 2886
		0.091 2.3	RX	1724 250	10699 2405
		0.079 2.0	RX	1600 232	9929 2232

NOTES

- RX = Roll Set for light wall stainless steel pipe marked with the prefix "RX"
- Std = Standard roll set marked with the prefix "R"
- C = Cut groove
- For pressure ratings on wall thicknesses not mentioned please contact Victaulic

5.1 PERFORMANCE (Continued)

Performance on ISO wall thicknesses

Nominal Size inches DN	Actual Outside Diameter inches mm	Pipe Wall Thickness inches mm	Groove Type	Maximum	
				Working Pressure kPa psi	End Load N lb
4 DN100	4.500 114.3	0.346 8.8	C	2241 325	22994 5169
		0.248 6.3	C	2241 325	22994 5169
		0.177 4.5	Std	2065 300	21224 4771
		0.142 3.6	Std	2065 300	21224 4771
		0.114 2.9	RX	2065 300	21224 4771
		0.102 2.6	RX	1896 275	19455 4374
		0.079 2.0	RX	1600 232	16413 3690
DN139.7	5.500 139.7	0.394 10.0	C	1600 232	24518 5512
		0.280 7.1	C	1600 232	24518 5512
		0.260 6.6	Std	1600 232	24518 5512
		0.260 6.6	C	1600 232	24518 5512
		0.248 6.3	Std/C	1600 232	24518 5512
		0.220 5.6	Std/C	1600 232	24518 5512
		0.197 5.0	Std	1600 232	24518 5512
		0.157 4.0	Std	1600 232	24518 5512
		0.134 3.4	RX	1207 175	18494 4158
		0.126 3.2	RX	1034 150	15852 3564
		0.110 2.8	RX	862 125	13113 2970

NOTES

- RX = Roll Set for light wall stainless steel pipe marked with the prefix "RX"
- Std = Standard roll set marked with the prefix "R"
- C = Cut groove
- For pressure ratings on wall thicknesses not mentioned please contact Victaulic

## 6.0 NOTIFICATIONS

### WARNING

- Victaulic RX roll sets must be used when grooving light-wall/thin-wall stainless steel pipe for use with Victaulic Couplings.

Failure to use Victaulic RX roll sets when grooving light-wall/thin-wall stainless steel pipe may cause joint failure, resulting in serious personal injury and/or property damage.

### NOTICE

- Victaulic RX grooving rolls must be ordered separately. They are identified by a silver color and the designation RX on the front of the roll sets.

### General Notes

Working Pressure and End Load are total, from all internal and external loads, based on stainless steel pipe, roll grooved with Victaulic rolls in accordance with Victaulic specifications. “RX” rolls must be used for Schedules 5S, 10S and 10. Standard rolls should be used for Schedule 40S and Standard Weight pipe. Contact Victaulic for performance on other pipe or cut grooved pipe. See [publication 24.01](#) for more information pertaining to tools.

WARNING: FOR ONE TIME FIELD TEST ONLY, the Maximum Joint Working Pressure may be increased to 1 ½ times the figures shown.

Metric thread size bolts are available for all coupling sizes upon request. Contact Victaulic for details.

WARNING: Depressurize and drain the piping system before attempting to install, remove, or adjust any Victaulic piping products.

This product shall be manufactured by Victaulic or to Victaulic specifications. All products to be installed in accordance with current Victaulic installation/assembly instructions. Victaulic reserves the right to change product specifications, designs and standard equipment without notice and without incurring obligations.

## 7.0 REFERENCE MATERIALS

[05.01: Gasket Selection Guide](#)

### User Responsibility for Product Selection and Suitability

Each user bears final responsibility for making a determination as to the suitability of Victaulic products for a particular end-use application, in accordance with industry standards and project specifications, and the applicable building codes and related regulations as well as Victaulic performance, maintenance, safety, and warning instructions. Nothing in this or any other document, nor any verbal recommendation, advice, or opinion from any Victaulic employee, shall be deemed to alter, vary, supersede, or waive any provision of Victaulic Company’s standard conditions of sale, installation guide, or this disclaimer.

### Intellectual Property Rights

No statement contained herein concerning a possible or suggested use of any material, product, service, or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Victaulic or any of its subsidiaries or affiliates covering such use or design, or as a recommendation for the use of such material, product, service, or design in the infringement of any patent or other intellectual property right. The terms “Patented” or “Patent Pending” refer to design or utility patents or patent applications for articles and/or methods of use in the United States and/or other countries.

### Note

This product shall be manufactured by Victaulic or to Victaulic specifications. All products to be installed in accordance with current Victaulic installation/assembly instructions. Victaulic reserves the right to change product specifications, designs and standard equipment without notice and without incurring obligations.

### Installation

Reference should always be made to the Victaulic installation handbook or installation instructions of the product you are installing. Handbooks are included with each shipment of Victaulic products, providing complete installation and assembly data, and are available in PDF format on our website at [www.victaulic.com](http://www.victaulic.com).

### Warranty

Refer to the Warranty section of the current Price List or contact Victaulic for details.

### Trademarks

*Victaulic* and all other Victaulic marks are the trademarks or registered trademarks of Victaulic Company, and/or its affiliated entities, in the U.S. and/or other countries.